



CheckBox HSv430 Specifications & Features

Release 4.96 and up

The CheckBox HSv430 is a self-contained, stand alone guest Internet solution, ideal for motels, inns, restaurants, bars, marinas, function halls and more. The HSv430 works with any high speed Internet connection and does not require a dedicated computer.

All CheckBox HSv430 Systems Feature:

- ☑ Up to three wireless networks from one controller and one set of access points
- ☑ Includes S/A/F/E The Survey And Feedback Engine
- ☑ Captive portals for up to two different guest networks
- ☑ A separate encrypted network for management and property use
- ✓ Supports wired and wireless clients
- ☑ Splash page and redirect page fully configurable no vendor banner ads or logos required
- ☑ Splash page can be location or region specific
- ☑ Splash page can be dynamically updated with your current CMS (content management system)
- ☑ Domain White List allow access to pre-specified domains without validation
- ☑ Multiple validation options tickets, limited or unlimited free access, credit cards & Perma codes
- ☑ Property Management Integration Supports integration with Property Management Systems
- ☑ Participant loyalty/rewards program capable with provided API
- ☑ VPN support for end clients for connecting to corporate clients
- ✓ Supports roaming among AP's
- ☑ Compatible with all Operating Systems No configuration changes required on guest devices
- ✓ Support for static IP clients
- ☑ Supports self-correcting mesh architecture with redundant connections between nodes
- ☑ Self-configuring architecture supports wireless & wired mesh nodes for rapid, low cost deployment
- ☑ Client-to-Client security isolation supported
- ☑ Bandwidth throttling and management
- ☑ Torrent inhibiting control
- ☑ System firewall to protect guests from external threats
- ☑ Tunneling VPN for easy management without port forwarding, static IP's, or manual DMZ settings
- ☑ Easily operates outside of corporate telecommunication infrastructure for PCI compliance
- ☑ Can be used with external content filtering services
- ☑ Web based administrative tools
- ☑ Remote access for off-site property management
- ☑ 24/7 monitoring with text or email notifications of outages
- ✓ Automatic software upgrades
- ☑ SMTP redirect available
- ☑ Live 24/7 Guest Support available

Specifications

Management Web based GUI 4 Gigabit Ports (1 WAN, 3 LAN) Power requirements 120 to 240VAC ~10 watts Operating temp 0 ~ 70.C